

Technical Data Sheet

UNICOLL EXTRA

High quality polymer modified cement based tile adhesive

Description :

UNICOLL EXTRA is used for bonding mosaic, ceramic tiles and natural stones on floors and walls, indoors and outdoors. Also used for bonding tiles in swimming pools, tiles on tiles, tiles on gypsum boards and tiles on emulsion paints.

Precautions :

For exterior facades use UNICOLL EXTRA for tile dimensions up to 40x40cm.

For tile dimensions up to 60x60cm on facades use UNICOLL FLEX + UNICRETE AR, or UNICOLL SUPER

Instructions for use :

All flat substrates should be free of loose particles, grease, oil etc...

Mortar substrates should have cured completely before the application of the tile adhesive.

Each 20 Kgs tile adhesive powder should be mixed with about 6 liters of clean water in a clean container till it becomes a homogeneous paste.

It is preferable to pour the water into the container first then add the tile adhesive powder. Also it is advisable to use an electrical drill to get consistent mixing.

The tile adhesive paste should be left to stand for about 5 minutes then stirred again and applied on the substrate with a notched trowel.

At least 70% of the back of the tiles should be covered by the tile adhesive paste for internal and light traffic areas and 100% for external and high traffic areas.

Technical data:

- **Color** : White
- **Potlife** of the tile adhesive paste: approx. 3 hrs at normal ambient temperature.
- **Coverage** : approx. 3 – 6 Kgs powder per square meter depending on the type of substrate and tile dimensions.
- **Open time** of the tile adhesive paste : approx. 30 minutes after bedding-in.
- **Tensile Strength** of the hardened adhesive after 28 days : 1.90 N/mm²
- **Packing** : 20 Kgs bags
- **Storage** : At least 12 months in a dry place in the sealed original packing.