

UNICOLOR

Waterproof coloured tile grout

Description :

UNICOLOR is used for grouting joints between ceramic and mosaic tiles laid on floors and walls in internal areas. It is waterproof and the colours are lightstable. UNICOLOR 0-4mm is for joints up to 4mm width while UNICOLOR 4-20mm is for joint widths between 4 & 20mm.

Precautions :

For exterior applications UNICOLOR Extra is recommended.

Instructions for use :

The joints must be clean, free from dust, adhesive or mortar.

The outside temperature should be between 5 degC and 35 degC.

Grouting should be executed after 1 day of the curing of the cement tile adhesive or 1 week after the curing of the cement-sand mortar.

Each 5 Kgs tile grout powder should be mixed with about 1.50 liters of clean water in a clean container till it becomes a homogeneous paste.

It is preferable to pour the water into the container first then add the tile grout powder. Also it is advisable to use an electrical drill to get consistent mixing.

The tile grout paste should be left to stand for about 5 minutes then stirred again and applied to fill the tile joints using a rubber or metal spatula.

The tile surfaces can be cleaned with a humid sponge before the hardening of UNICOLOR (after 15-30 minutes). Once UNICOLOR grout has hardened, the tile surfaces can be cleaned with a dry cloth.

Technical data:

- **Color** : 40 colours available (+ others on demand)
- **Potlife** of the tile grout paste: approx. 30 minutes at normal ambient temperature.
- **Coverage** : Depends on the joint widths and tile dimensions.
- **Packing** : 5 Kgs bags
- **Storage** : At least 12 months in a dry place in the sealed original packing.