

UNICRETE AR

Synthetic latex additive for UNICOLL FLEX

Description :

UNICRETE AR is a specially formulated Synthetic latex be added to UNICOLL FLEX tile adhesive. It increases the adhesion, flexibility , water repellency and resistance to thermal shocks. It replaces mixing water and the mix is mainly used for exterior terrace and facade tiles up to 60x60cm.

Precautions :

Do not use UNICOLL FLEX + UNICRETE AR for high moisture unstable stones.

Instructions for use :

Substrates should be solid, not subject to shrinkage, free from dust and loose materials, and free from oil, grease, wax and paint.

In case of hot weather, substrates should be dampened with water to improve the cement hydration and adhesion.

Each 20 Kgs UNICOLL FLEX should be mixed with 5 Kgs of UNICRETE AR in a clean container till it becomes a homogeneous paste.

It is preferable to stir the UNICRETE AR and pour it into the container first then add the UNICOLL FLEX. Also it is advisable to use an electrical drill to get consistent mixing.

The tile adhesive paste should be left to stand for about 5 minutes then stirred again and applied on the substrate.

Technical data:

- **Color** : White
- **Dosage** : 5 Kgs UNICRETE AR to be mixed with 20 Kgs UNICOLL FLEX.
- **Packing** : 5 Kgs gallons
- **Storage** : At least 12 months in a dry place in the sealed original packing.